

Q8 Holbein HP SE BIO 46

Eco-friendly saturated synthetic ester-based hydraulic oil

Description

Q8 Holbein HP SE Bio 46 is a superior synthetic saturated ester based lubricant that assures a long service lifetime and energy efficiency. The lubricant is readily biodegradable (>70 in 28 days) and is used in sensitive area's where the impact on the environment must be limited. Q8 Holbein HP Bio SE 46 has a very high viscosity index which leads to excellent flow properties in all temperatures.

Applications

Q8 Holbein HP SE Bio 46 is perfect for applications in rough hydraulic systems in environmental sensitive area's and all temperatures like agriculture, forestry, water works, marine and construction.

Benefits

- Eco-friendly and limited impact on the environment
- Doesn't contain hazardous components
- Readily biodegradable
- Zinc-free additives
- Extensive oil drain interval for a longer lubricant lifetime
- Excellent synthetic oil
- Outstanding oxidation stability
- Exceptional thermal durability

Specifications & Approvals

Bosch Rexroth	RE 90221 notes	ISO	11158 HV
DIN	51524-3 HVLP	ISO	15380 HEES

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	0,914
Kinematic Viscosity, 40 °C	D 445	mm ² /s	48.8
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.85
Viscosity Index	D 2270	-	185
Total Acid Number	D 974	mg KOH/g	0.71
Iodine value	-	-	< 5
Pour Point	D 97	°C	< -54
Flash Point, COC	D 92	°C	246
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1a
Biodegradability, 28 days	OECD 301 B	%	>70
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

The energy efficiency is only valid when compared to Q8 standard hydraulic lubricants. The used technology has been tested under controlled circumstances. Improvements of the energy efficiency may vary based on applications and operating conditions.