

Q8 Ravel BW

Low viscosity short-term rust preventive fluid

Description

Q8 Ravel BW is a low viscosity rust preventive fluid for short-term corrosion protection of non-ferrous and ferrous components such as steel strips sheets. It is specifically designed for use in indoor intermediate storage applications. Depending on the application method, the product will leave an oily protection film. The product is free of solvents and has a high flash point, guaranteeing a minimal fire hazard and improved operator working conditions.

Applications

Q8 Ravel BW is a high quality indoor protection fluid for the protection of non-ferrous and ferrous components and assemblies where the use of a solvent cutback product is not permitted because of fire hazards. The film provides effective short-term protection against corrosion especially for indoor intermediate storage. The Q8 Ravel BW can be applied by dipping, rolling or spraying leaving a thin oily layer. The water removing properties are more effective when the components are dipped into the oil tank. It can be easily removed with a solvent or alkaline cleaner.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from frost and direct sunlight.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright & Clear
Density, 15 °C	D 4052	g/ml	0.87
Kinematic Viscosity, 40 °C	D 445	mm ² /s	27
Flash Point, P-M	D 93	°C	198

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.