PRODUCT DATA SHEET

Q8 Bach XNK

High performance, neat metal cutting oil

Description

Q8 Bach XNK is a chlorine free, non-active, low viscosity performance neat cutting oil specially developed for honing operations.

Applications

Q8 Bach XNK is a first choice product for honing and light machining operations.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from water entry, frost and direct sunlight.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

| | Method | Unit | Typical | |
|----------------------------|--------|-------|---------|--|
| Density, 15 °C | D 4052 | g/ml | 0.818 | |
| Density, 20 °C | D 4052 | g/ml | 0.815 | |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 4.7 | |
| Flash Point, COC | D 92 | °C | 130 | |
| Colour | D 1500 | - | L 0.5 | |
| Copper Strip, 3 h, 100 °C | D 130 | - | 1b | |
| Four Ball Test, Weld Load | IP 239 | kg | 300 | |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q80ils representative for further advice and support on your specific application and equipment.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Bach XNK is $1.23\,\mathrm{kg}$ CO $_2\mathrm{eq}$ / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

