

Q8 Brahms 2240

Forming oil for the high demanding forming operations on fasteners

Description

Q8 Brahms 2240 is a special developed medium viscosity, chlorine-free, non-active type metal forming oil, containing lubricity- and Extreme Pressure-additives.

Applications

High demanding forming operations on fasteners.

User instructions

In order to preserve the integrity of this product, drums should be stored inside a building protected from frost and direct sunlight.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0.89
Kinematic Viscosity, 40 °C	D 445	mm ² /s	68
Flash Point, COC	D 92	°C	210
Copper Strip, 3 h, 100 °C	D 130	-	1
Four Ball Test, Weld Load	IP 239	kg	470

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Brahms 2240 is **1.30** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

