

Q8 Brunel XF 280

Advanced performance semi-synthetic biostable ester based water soluble cutting fluid for heavy duty machining

Description

Q8 Brunel XF 280 is an advanced ester based water soluble cutting and grinding fluid for all heavy duty machining. It forms a semi-translucent emulsion when mixed with water and it is very low foaming and tramp oil rejecting. Q8 Brunel XF 280 has an excellent chemical and biological stability and offers a high detergency and advanced cleanliness. Its high ester content makes the fluid highly polar to surfaces, providing a very high lubricity that substantially increases tool life and surface finish.

Applications

Q8 Brunel XF 280 being a multi-material application product is recommended for all heavy duty machining applications on steel alloys, copper alloys, stainless steel, Inconel, titanium alloys and aluminium alloys, in particular 6000 and 7000 series.

User instructions

1. The correct mixing procedure is to add Q8 Brunel XF 280 to water and stir. For this operation we recommend positive displacement (Dosatron type) mixing units.
2. In order to preserve the integrity of this product drums should be stored inside a building protected from frost and direct sunlight.
3. Recommended concentrations are listed below.

High performance machining and tapping	6 – 10%
Severe machining	8 – 12%

Note: In some circumstances and applications, it is beneficial to exceed the recommendations shown above.

Environment, Health and Safety

Q8 Brunel XF 280 is free of added formaldehyde, chlorine, boron, boric acid and secondary amines. It is compliant with the TRGS 611 specification. This ensures environmental safety & operator health. Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Appearance (Emulsion)	Visual	-	Semi-translucent
Appearance (Concentrate)	Visual	-	Amber
Density, 20 °C	D 4052	kg/l	0.95
pH@5% in 400 ppm CaCO ₃ in water	E 70	-	9.5
Refractometer Factor	-	-	0.9
Corrosion characteristics of water-mix metalworking fluids	IP 125	%	3%
Determination of rust prevention characteristics of water-mix metalworking fluids	IP 287	%	6%

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.