

Q8 Haydn 32

Advanced zinc-based hydraulic oil

Description

Q8 Haydn 32 oil consists of a zinc-based additive technology. This oil can be used in all sorts of operational applications and industrial equipment. Q8 Haydn 32 oil has an optimum thermal and oxidation stability and has a long service life time.

Applications

Q8 Haydn 32 is suitable for all kinds of systems, general industrial hydraulic applications and other industrial applications (low charged gears, pumps, compressors, bearings).

Benefits

- · Lower downtime and an improved maintenance efficiency
- · Zinc-based additives
- Advanced performance against wear
- Excellent separation of water
- · Advanced release of entrained air bubbles

Specifications & Approvals

 Bosch Rexroth
 RE 90220 notes
 ISO
 11158 HM

 DIN
 51524-2 HLP
 MAG IAS
 P-68, P-69, P-70

 Denison
 HF-0, HF-1, HF-2
 Swedish Standard
 SS 155434 AM

Eaton Brochure 03-401-2010

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0,875
Density, 20 °C	D 4052	g/ml	0,871
Kinematic Viscosity, 40 °C	D 445	mm²/s	32
Kinematic Viscosity, 100 °C	D 445	mm²/s	5.5
Viscosity Index	D 2270	-	105
Pour Point	D 97	°C	-33
Flash Point, COC	D 92	°C	210
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(10)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/20/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1
FZG Test. A/8.3/90	DIN 51354	load stage	10

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Haydn 32 is $1.25\,\mathrm{kg}\,\mathrm{CO}_2\mathrm{eq}$ / kg. Please contact Q80ils to learn more about the positive environmental impact, the

handprint, of this product.
To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.
For more info check here

