

Q8 Allroads 4T 10W-40

Excellent synthetic motorcycle oil

Description

Q8 Allroads 4T 10W-40 is an excellent synthetic motorcycle oil that matches various driving conditions. Its robust formulation provides a strong film on all moving parts to guarantee an outstanding wear protection and gear pitting in all driving conditions. Q8 Allroads 4T 10W-40 exceeds the top international OEM requirements.

Applications

Q8 Allroads 4T 10W-40 is used in on-road motorcycles (daily transportation) and off-road motorcycles with dry or wet clutch. It is used in both air and water cooled engines.

Benefits

- Excellent engine performance at extreme driving conditions.
- Outstanding year round properties.
- Excellent protection against rust and corrosion.
- Outstanding bearing lubrication and cylinder wear protection.
- Excellent cleanliness and wear protection for all components.

Specifications, recommendations and approvals

API SL JASO MA2

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0,861
Density, 15 °C	D 4052	g/ml	0,864
Viscosity Grade	-	-	10W-40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	98
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.3
Viscosity Index	D 2270	-	150
Pour Point	D 97	°C	-39
Flash Point, COC	D 92	°C	231

The figures above are not a specification. They are typical figures obtained within production tolerances.