

Q8 Auto CVT EVO

Synthetic CVT transmission fluid

Description

Q8 Auto CVT EVO is an outstanding multi-vehicle Continuous Variable Transmission fluid for modern transmissions. This product is shear stable, offers extended drain intervals, excellent performance reserve and prevents slipping belts/clutches and breakdowns. It maintains high steel-steel friction and oil pressure, and provides a strong oil film.

Applications

Q8 Auto CVT EVO is applicable for CVT transmissions in passenger cars. It meets the JASO LVFA specification. The product is based on new technology and exceeds the requirements of all major OEMs such as Toyota, Nissan, Mitsubishi, Subaru, Suzuki, Hyundai, Honda, Daihatsu, Mini, BMW, Chrysler and GM.

Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.
- Excellent metal-metal friction and torque transfer
- Excellent oxidation and thermal stability
- Incorporates well balanced friction modifier system

Specifications, recommendations and approvals

Aisin Warner	JWS 3401	Nissan	Altima Hybrid with eCVT
BAIC	CVTF-EX1	Nissan	KTF-1
BMW/MINI	83 22 0 136 376	Nissan	N-CVT
BMW/MINI	83 22 0 429 154	Nissan	NS-1
BMW/MINI	EZL 799	Nissan	NS-2
BMW/MINI	EZL 799A	Nissan	NS-2V
BMW/MINI	ZF CVT V1	Nissan	NS-3
Chery	CVT	Nissan	e Power
Chery	CVT 25	Opel/Vauxhall	7-speed CVT
Chrysler	CVT+4	Opel/Vauxhall	95529854
Chrysler	NS-2	PSA	Standard 9735EF
DFSK	CVTF-EX1	Punch	CVTF-EX1
Daihatsu	Ammix CVTF DFE	Punch	CVTF-EX1
Daihatsu	Ammix CVTF DC	Punch	VT2
Daihatsu	Ammix CVTF DFC	Punch	VT3
Daihatsu	Fluid TC	Punch	VT5
Dodge	CVTF+4	Renault	Matic CVT
Dodge	NS-2	Renault	Matic CVT CK
Fiat	Tutela Car CVT NG	Renault	Matic CVT FK
Ford	Escape Hybrid eCVT	Renault	Matic CVT SK
Fujijyuuko	i-CVTF FG	Saturn	CVTF I-Green2
GM	1940713	Saturn	DEX-CVT
GM	1940714	Shell	Green 1V
GM	CVTF I-Green2	Subaru	CV-30
GM	DEX-CVT	Subaru	ECVT
GM	HP CVT	Subaru	High Torque CVTF-LV
GM	VT 40	Subaru	K0421Y0700
Honda	CVT	Subaru	K0425Y0710
Honda	Fit	Subaru	K0425Y0711
Honda	HCF2	Subaru	Lineartronic Chain CVT 3 Fluid
Honda	HMMF	Subaru	Lineartronic High Torque (HT) CVT Fluid
Honda	Jazz	Subaru	Lineartronic chain CVT
Honda	Z-1 (CVT model)	Subaru	Lineartronic chain CVT II Fluid

Honda	e-HEV	Subaru	NS-2
Honda	iMMD	Subaru	iCVT
Hyundai/Kia	CVT-1	Subaru	iCVT FG
Hyundai/Kia	CVT-J1	Suzuki	CVT Green 1
Hyundai/Kia	SP CVT-1	Suzuki	CVT Green 1V
Hyundai/Kia	SP-III (CVT model)	Suzuki	CVT Green 2
Idemitsu	CVTF-EX1	Suzuki	CVTF 3320
JASO	M315 Type 1A	Suzuki	CVTF 4401
Jatco	CVT 8 Hybrid	Suzuki	CVTF TC
Jatco	JR712E	Suzuki	NS-2
Jeep	CVT+4	Tesla	Model 3
Jeep	NS-2	Tesla	Model S
Lexus	Fluid FE	Toyota	CVTF FE
Lexus	Fluid TC	Toyota	CVTF TC
MB	236.20	Toyota	Noah
MG/Rover	EM-CVT	Toyota	Prius
Mazda	JWS 3320	Toyota	THS 5th Gen.
Mazda	SKYACTIVE-HYBRID	Toyota	THSII
Mitsubishi	CVTF ECO J4	Toyota	Voxy
Mitsubishi	CVTF-J1	VAG	Audi Multitronic
Mitsubishi	CVTF-J4	VAG	VW G 052 180
Mitsubishi	CVTF-J4+	VAG	VW G 052 516
Mitsubishi	Diaqueen CVT Fluid J1	VAG	VW TL 521 16
Mitsubishi	Diaqueen CVT Fluid J4	VAG	VW TL 521 80
Mitsubishi	Diaqueen CVT Fluid J4+	Volvo	CVT 4959
Mitsubishi	Diaqueen SP-III	Zotye	CVT
Mopar	CVT+4		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,849
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	7.0
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	32.3
Viscosity Index	D 2270	-	185
Brookfield Viscosity, -40 °C	D 2983	Pa.s	10
Flash Point, COC	D 92	°C	190
Pour Point	D 97	°C	-45

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Auto CVT EVO is **1.52 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

