

## Q8 Terra 4000 UTTO CVT 75W-85

Exceptional Synthetic Tractor Continuous Variable Transmission Fluid

### Description

Q8 Terra 4000 UTTO CVT 75W-85 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T Q8 Terra 4000 UTTO CVT 75W-85 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

### Applications

Q8 Terra 4000 UTTO CVT 75W-85 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

### Benefits

- Superior viscosity retention providing smoothless CVT operation.
- Best-in-class oxidation stability.
- Superior frictional properties for smooth brake operation.
- Superior response of hydraulic components.
- Maximum compatibility with conventional elastomers.

### Specifications, recommendations and approvals

|                  |                             |                 |                              |
|------------------|-----------------------------|-----------------|------------------------------|
| AGCO             | CVT ML 200                  | Massey Ferguson | CMS M 1141 / M 1143 / M 1145 |
| API              | GL-4                        | New Holland     | NH 410-B / NH 410-C          |
| Case             | MS 1206                     | Same Deutz Fahr | UTTO                         |
| Case             | MS 1207                     | Valtra          | G2-08 (XT-60)                |
| Case             | MS 1209                     | Valtra          | G2-B10 (XT-60+)              |
| Case             | MS 1210                     | ZF              | TE-ML 03E / 03G / 03L        |
| Case New Holland | MAT 3505                    | ZF              | TE-ML 05F                    |
| Case New Holland | MAT 3525                    | ZF              | TE-ML 06B                    |
| Case New Holland | MAT 3540                    | ZF              | TE-ML 06D                    |
| Case New Holland | MAT 3541                    | ZF              | TE-ML 06E                    |
| Case New Holland | MAT 3544                    | ZF              | TE-ML 06F                    |
| Case New Holland | MAT 3552-A                  | ZF              | TE-ML 06K                    |
| Case New Holland | MAT 3553-A                  | ZF              | TE-ML 06L                    |
| Caterpillar      | SATO                        | ZF              | TE-ML 06M                    |
| Claas            | CVT                         | ZF              | TE-ML 06N                    |
| Deutz            | Allis AC Power Fluid 821 XL | ZF              | TE-ML 06P                    |
| Fendt            | FWN 81001                   | ZF              | TE-ML 06R                    |
| Fendt            | Vario                       | ZF              | TE-ML 06S                    |
| John Deere       | JDM J20C                    | ZF              | TE-ML 06T                    |
| Komatsu          | KES 07.866                  | ZF              | TE-ML 17E                    |
| Kubota           | UDT / Super UDT / UDT-HD    | ZF              | TE-ML 21F                    |
| Massey Ferguson  | CMS M 1135                  |                 |                              |

## Properties

|                              | Method   | Unit               | Typical |
|------------------------------|----------|--------------------|---------|
| Viscosity Grade              | SAE J300 | SAE                | 10W-30  |
| Viscosity Grade              | SAE J306 | SAE                | 75W-85  |
| Density, 15 °C               | D 4052   | g/ml               | 0,861   |
| Density, 20 °C               | D 4052   | g/ml               | 0,858   |
| Kinematic Viscosity, 40 °C   | D 445    | mm <sup>2</sup> /s | 71.1    |
| Kinematic Viscosity, 100 °C  | D 445    | mm <sup>2</sup> /s | 12.0    |
| Viscosity Index              | D 2270   | -                  | 166     |
| Brookfield Viscosity, -20 °C | D 2983   | mPa.s              | 3400    |
| Pour Point                   | D 97     | °C                 | -42     |
| Flash Point, COC             | D 92     | °C                 | 240     |

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 4000 UTTO CVT 75W-85 is **1.30** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

