

Q8 da Vinci 8

Demoulding oil with exceptional surface finishing

Description

Q8 da Vinci 8 is a superior demoulding oil with anti-rust inhibitors for steel moulds. It's solvent free and easily applicable. The reactive layer in the oil creates a layer between the concrete and the mould and contains additives for a clean demoulding. Q8Oils claims that Q8 da Vinci provides an exceptional smooth surface finish of the concrete and a clean mould without staining or dust.

Applications

Q8 da Vinci 8 is used for demoulding of concrete foundation piles and on-site elements (vertical and warm moulds) such as floors, stairs and balconies. It is applied in steel and plywood moulds. Q8 da Vinci 8 is highly recommended on site building constructions and also suited for direct release demoulding.

Benefits

- Leads to an improved durability of the finished product quality
- Outstanding quality of the surface
- Extremely effective demoulding operation
- · Light colour
- Exceptional anti-rust properties
- Enhanced with special additives
- Prevents sticking
- Extremely handy to apply

Properties

	Method	Unit	Typical	
Appearance	Visual	-	Bright and Clear	
Density, 20 °C	D 4052	g/ml	0,84	
Kinematic Viscosity, 40 °C	D 445	mm²/s	8.0	
Pour Point	D 97	°C	-15	
Flash Point, COC	D 92	°C	140	
Rust Test, Proc. A and B, 24 h	D 665	-	pass	

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

For use in cold temperatures, we recommend Q8 da Vinci P series. Q8 da Vinci range should be applied evenly and sparingly by low-pressure spray or brush onto a dry surface, ideally immediately after stripping. A second coat may be necessary when used on new timber or untreated wood.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 da Vinci 8 is 1.25 kg CO₂eq / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

