

Q8 Formula Top Up 5W-30

Description

Ultra-High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil. This product offer protection against Low-Speed Pre-Ignition (LSPI) as well as compatibility with Gasoline Particulate Filters (GPF). It delivers superior fuel economy and engine protection for diesel and gasoline engines while being compatible with biofuels.

Applications

Top Up for all passenger car brands.

Specifications, recommendations and approvals

ACEA
API
Abarth
BMW
Chrysler
Fiat
Ford
GM
ILSAC

Jaguar Land Rover
MB
Opel/Vauxhall
PSA
Porsche
Renault
Toyota
VAG

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,861
Kinematic Viscosity, 40 °C	D 445	mm ² /s	69.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12.0
Viscosity Index	D 2270	-	173
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	3.7
Apparent Viscosity, -30 °C	D 5293	mPa.s	5600
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	209

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Only for Top Up.