

Q8 Unishift PC Synt 75W

Synthetic API GL-4 manual transmission fluid

Description

Q8 Unishift PC Synt 75W is a superior manual transmission fluid for passenger cars and light duty vehicles. This versatile lubricant offers exceptional protection and durability, even under extreme pressure, and provides best-in-class thermal stability, making it suitable for a wide variety of passenger car applications. It meets the requirements of most OEMs based on API GL-4.

Applications

Q8 Unishift PC Synt 75W is a versatile lubricant designed to be used in passenger cars and light duty synchromesh manual gearboxes and transaxles, specifically in high load carrying situations. It meets the API GL-4 specification and the requirements of most European and Asian manufacturers.

Benefits

- Exceptional low temperature fluidity and wide temperature operating range.
- Exceptional internal friction reduction.
- Excellent easy gear shifting at low temperatures.
- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

| | | | |
|-----------------|--------------|------------|--------------------------------|
| API | GL-4 | PSA | 9730-A8 |
| BMW/MINI | JWS 2271 | PSA | B71 2310 |
| BMW/MINI | MTF-LT2 | VAG | VW G 052 171 |
| BMW/MINI | MTF-LT3 | VAG | VW G 052 512 |
| Fiat | 9.55550-MZ14 | VAG | VW G 052 527 |
| Fiat | 9.55550-MZ2 | VAG | VW G 052 527 |
| Fiat | 9.55550-MZ27 | VAG | VW G 052 549 |
| Fiat | 9.55550-MZ6 | VAG | VW G 052 798 |
| Ford | M2C200-D1 | VAG | VW G 52 726 |
| Ford | M2C200-D2 | VAG | VW TL 521 71 (G 052 171 A1/A2) |
| GM | MTF 0063 | VAG | VW TL 521 78 (G 052 178 A2) |
| MB | 235.71 | VAG | VW TL 525 12 (G 052 512 A2) |

Properties

| | Method | Unit | Typical |
|------------------------------|--------|--------------------|---------|
| Density, 15 °C | D 4052 | g/ml | 0,847 |
| Viscosity Grade | - | - | SAE 75W |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 33 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 6.8 |
| Viscosity Index | D 2270 | - | 172 |
| Brookfield Viscosity, -40 °C | D 2983 | Pa.s | 44 |
| Pour Point | D 97 | °C | -39 |
| Flash Point, P-M | D 93 | °C | 195 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Unishift PC Synt 75W is **1.38** kg CO₂eq / kg.*

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**